

N 49° E 1 1/2 Links and Beech 12 Ins. dia. S. 59° W 20 1/2 Links Then
N 13 1/2° E 6.57 chains to the place of Beginning Containing
8 Acres.

Aaron Bland and } Chain Bearers.
B. C. Ballard

John B. Kelshaw C. S. C. C. Ia.

No 3. November the 29th 30th December the 1st 2nd 1837.

Surveyed for Willis Barton in T. 8. N. R. 5 W. Section 18 In
west half of said section to wit, S. W 1/4 W 1/2 of N. W 1/4 and
N. E. 1/4 of N. W 1/4. After the said Barton Produced the
following proof of the following Notification
(Copy of notification). State of Indiana Greene County, You
are hereby notified that I expect to have the county
Surveyor on the 29th day of November 1837 on Section 18
Township 8 North of Range 3 West In order to Establish the
corners of the following parts of said Section, to wit, the
South W. 1/2 of N. W. 1/4 & N. E. 1/4 of N. W. 1/4 and to
continue from day to day till the same be complete
Nov. 14th 1837 Willis Barton.

Here follows a copy of Proof of notification

State of Indiana Greene County Smith Township
I, Personally appeared before me Joseph Smith a Justice
of the peace in Township and County aforesaid James Fry
of said Township and Being duly sworn deposes and
saith that he served a copy of the within Notification
on Hiram Hicks, Willis Hicks, John Shoemaker, Terry Raily and
John Allison on the 14th day of November 1837 and further
he saith not

James ^{his} Fry
mark.

Sworn and Subscribed to before me this 1st day of
December 1837. Joseph Smith J. P. (seal)

Beginning on the South side of Section at the quarter stake
then S. 85° W.

No 4. December the 4th and 5th days 1837 Then
Surveyd for Robert Inman and Samuel Dixon Both
parties being present Agreed to have the division line
that here follows run at N 83 1/2° E Supposing that this
course would square on the N and S. Section line. Rather
than go to the trouble of Trying the variation of the out-
side lines. Beginning at the quarter stake on the
West side of fractional Section No. 33. T. 8. N. R. 5 W and
run thence N 83 1/2° E 59.64 Poles into the Goose pond and
made a corner or rather supposed a corner for the beginning
corner then continued same course 129.36 poles to a stake
at an Elm 6 Ins. dia. N 15° W 81 Links and Black walnut
20 Ins. dia. N 61° W 40 Links then N 6 1/2° W 18 1/2 poles to a stake
at an Elm 15 Ins. dia. S 64° W 33 1/2 Links and Elm 8 Ins. dia.
S. 24° W 38 1/2 Links Then S. 83 1/2° W. 38 poles to a stake at a
Hickory 16 Ins. dia. S 67 1/4° E 56 Links and Ash 8 Ins. dia. N. 58 1/2° E
53 Links Then N 73 1/4° W 72 poles to a stake at a White
Walnut 8 Ins. dia. S. 32° W 19 Links and white walnut
14 Ins. dia. S. 52° E 42 Links then N 65 1/2° W 32 poles to a
stake at an Ash 7 Ins. dia. S 81° E 46 Links and Ash 5
Ins. dia. N 37 1/2° E 31 Links. Then S. 8 1/2° E 62.50 poles to
place of beginning in Goose Pond.

For the convenience of after Surveyors that
the lines on the North part of the foregoing Survey
are run in the South side of a Bay.

Ephraim Herring } Chain Bearers
And Woodsworth)
John B. Kelshaw C. S. C. C. Ia.

No 5

January the 18th day 1838 Surveyed for James
Jamison T. 8. N. R. 5 W. West Fraction 28 Beginning at the N. W.
corner of said fraction Then S. 6 1/2° E 160 poles to a corner
nearly East of the South east corner of the Widow Dixons
porch and from thence run the division line between
the North and South half of said fraction. N 88°
E 146 poles to the bank of White river then run.